



Basic equipment:

- * Aluminium welded-frame boat Powerboat. (German aluminium 3mm and bottom 4 mm, grade 5083).
- * Back console with two folding seats and two storage boxes is formed under the rear platform.
- * Front platform - one 450 l double-door storage box with a possibility to install an aerator.
- * Two spinning place and storage pockets on both sides of the boat (LED illumination)
- * All storage boxes are dry-type and with a self-drain system.
- * The boat is fitted with an automatic water suction pump, mounting frame for fasten-type holders.
- * Transportation loops at the front and at the back and two places for fitting echo-sounders.
- * Aluminium fuel tank with breather 95 l
- * Preparation for mounting echosounder, trolling motor and electric anchor winch
- * Plastic 12 V power outlet
- * USB-outlet
- * Fishing platforms and floors are coated with marine vinyl coat, sides are sewed with fitted carpet.
- * 2 Plastic cup holder

Photo	Name	Price, € with VAT
	PowerBoat 500 with basic equipmennt	13 396,79
Optional equipment:		
	Low boat seat. Aluminium stand, fitting base. The seat is filled with special foam and coated with marine lether..	197,35
	Height-adjustable seat bumper 450 h	86,52
	Hi boat seat. Aluminium stand, fitting base. The seat is filled with special foam and coated with marine lether.	486,16
	Aerator with recirculating water pump 100 l. (Aluminium grade 5083). Completed with boat 475.	385,69
	3-step ladder. Stainless steel	83,31
	Moisture-resistant transportation tent with UV protection (breathing).	431,97
	Non-standard boat colour according to RAL colour chart. Standard color (Black, Red, Grey, Aluminium)	178,00
	"Motor guide" installation works with installation materials.	147,02


	Respo trailer for PowerBoat 500	1 733,60
	Set of fastening belts.	70,39
	Trailer bridges (set of 3 units)	91,82
	Pearl paint colour according to RAL colour chart.	252,00
	Pedestal Boat Seat Base	45,74

* Prices are with VAT.

* Boat production term - 60 business days from the day of receipt of advance payment.

* Contact details: Žilvinas Žalėnas, +370 687 89819, zilvinas@fishmaster.lt





TECHNICAL CHARACTERISTICS AND COMPOSITION

Length	5000
Width	2100
Height of the board	1000
Min. recommended power HP	110HP
Max. recommended power HP	150 HP
Aluminum fuel tank capacity	95 L
Max. number of passengers	4 persons
Max. weight of passengers, engine and equipment	500 KG
Aluminum thickness	3-4 mm
Height of trans	510
Kiel	21/16 degrees
Weight	550 KG
Maximum weight	1200 KG

CONSTRUCTION AND EXTERIOR

3-4mm German 5083 aluminum welded housing;
 Special top profile with integrated fasten holder system;
 Foam-filled body for maximum beach and safety;
 Tracking front and rear;
 Polyurethane painted or polished aluminum finish body.

INTERIOR

The deck of the ship has a useful area of 9.2 m²;
 Aluminum console with glass windshields;
 Steering wheel, gearbox, steering ropes are included;
 Built-in aluminum fuel tank 100 L;
 The ship's vans and platforms cover are optional: marine vinyl or caviar;
 2 ergonomically adjustable heights with aluminum racks, and two fastening tablets for ship chairs;
 Transformed rear platform with two folding seats and cup holders;
 Seat-support 900 h;
 All the seats are equipped with a special foam filler and a marine vinyl tapestry;
 Front platform with dry type two-door glovebox 450 L and aerator with 95 L recirculation;
 The floor is equipped storage for 5 battery's;
 Battery on the rear platform and storage for tarpaulin ;
 Each side of the ship is equipped with spin boxes and pockets (Led lighting);
 Hidden Type Hoods;
 Special transportation tarpaulin with UV protection.

SAFETY SYSTEMS

Automatic water pump SEAFLO live well 3028 L / h;
 The aerator filling pump SEAFLO drum 3028 L / h;
 Dry Type cases Self-Leakage system.

AUTOMATIC ANCHOR / ENGINE

Wiring and fastening locations are provided;
 MINN KOTA TERROVA I-PILOT 55 LBS (Recommended).

ELECTRICAL SYSTEM

Five-connector block with USB and 12 V connection;
 LED case lighting;
 Battery charging slot;
 Battery case;
 Navigation light;
 Channels for echo and automatic anchors are provided.

TRAILER

Modified single-axle Respo trailer 750V591L209;
 Galvanized steel frame;
 Internal dimensions (m) 5.90x2.09;
 Maximum weight 750 kg;
 Empty weight 276 kg;
 Maximum load of 474 kg;
 Calculated trailer load 900 kg;
 Spring suspension;
 Ski-type footrests covered with cobblestone cover for lighter removal / entry;
 800 kg load winch with 50 mm x 7.5 m belt;
 Supporting wheel with solid rubber tire, pipe diameter 48 mm,